

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau(43) International Publication Date
17 June 2004 (17.06.2004)

PCT

(10) International Publication Number
WO 2004/050572 A1(51) International Patent Classification⁷: C03B 37/018,
37/029(21) International Application Number:
PCT/FI2003/000934

(22) International Filing Date: 5 December 2003 (05.12.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
20022162 5 December 2002 (05.12.2002) FI(71) Applicant (for all designated States except US): NEX-
TROM HOLDING S.A. [CH/CH]; 29, rue de la Gare,
CH-1110 Morges (CH).

(72) Inventors; and


(75) Inventors/Applicants (for US only): HOVINEN, Anssi
[FI/FI]; Nummikuja 15, FIN-02730 Espoo (FI). KESÄLÄ,
Janne [FI/FI]; Puolarniitynkujä 4 A 1, FIN-02280 Espoo
(FI). SOININEN, Pekka [FI/FI]; Ilmarinkatu 10 B 28,
FIN-00100 Helsinki (FI).(74) Agent: SEPPÖ LAINE OY; Itämerenkatu 3 B,
FIN-00180 Helsinki (FI).(81) Designated States (national): AE, AG, AL, AM, AT (util-
ity model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA,CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (util-
ity model), DE, DK (utility model), DK, DM, DZ, EC, EE
(utility model), EE, EG, ES, FI (utility model), FI, GB, GD,
GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN,
MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU,
SC, SD, SE, SG, SK (utility model), SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.(84) Designated States (regional): ARIPO utility model (BW),
ARIPO patent (BW), ARIPO utility model (GH), ARIPO
patent (GH), ARIPO utility model (GM), ARIPO patent
(GM), ARIPO utility model (KE), ARIPO patent (KE),
ARIPO utility model (LS), ARIPO patent (LS), ARIPO
utility model (MW), ARIPO patent (MW), ARIPO utility
model (MZ), ARIPO patent (MZ), ARIPO utility model
(SD), ARIPO patent (SD), ARIPO utility model (SL),
ARIPO patent (SL), ARIPO utility model (SZ), ARIPO
patent (SZ), ARIPO utility model (TZ), ARIPO patent
(TZ), ARIPO utility model (UG), ARIPO patent (UG),
ARIPO utility model (ZM), ARIPO patent (ZM), ARIPO
utility model (ZW), ARIPO patent (ZW), Eurasian patent
(AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI,
SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR MAKING OPTICAL FIBRES

(57) Abstract: Method and apparatus for producing glass
products of predetermined shape. In the method, a preform
is introduced into a furnace and heated to a temperature above
the softening point of the glass. The heated portion is sub-
jected to tensile forces and drawn from the furnace through
an outlet opening. During processing, inert gas is fed into
the furnace. According to the invention, the concentration of
gaseous impurities in the furnace is maintained on the same
level as in the inert gas fed into the oven. To prevent inflow
of undesired gaseous components from the ambient air, a dif-
fusion barrier is established by generating a barrier flow of
inert gas in the inlet or outlet openings. This barrier flow
has a direction of flow, which is opposite to the direction of
the diffusion. The invention provides non-contacting sealing
between the furnace the preform while optimizing the con-
sumption of protective gas. The invention also allows for
simultaneous rotation of the preform.